

Table 1 Dimensions and Weights of Welded and Seamless Wrought Steel Pipe

NPS [Note (1)]	Customary Units			Identification [Standard (STD), Extra-Strong (XS), or Double Extra Strong (XXS)]	Schedule No.	DN [Note (2)]	SI Units		
	Outside Diameter, in.	Wall Thickness, in.	Plain End Weight, lb/ft				Outside Diameter, mm	Wall Thickness, mm	Plain End Mass, kg/m
1/8	0.405	0.049	0.19	...	10	6 (3)	10.3	1.24	0.28
1/8	0.405	0.057	0.21	...	30	6 (3)	10.3	1.45	0.32
1/8	0.405	0.068	0.24	STD	40	6 (3)	10.3	1.73	0.37
1/8	0.405	0.095	0.31	XS	80	6 (3)	10.3	2.41	0.47
1/4	0.540	0.065	0.33	...	10	8 (3)	13.7	1.65	0.49
1/4	0.540	0.073	0.36	...	30	8 (3)	13.7	1.85	0.54
1/4	0.540	0.088	0.43	STD	40	8 (3)	13.7	2.24	0.63
1/4	0.540	0.119	0.54	XS	80	8 (3)	13.7	3.02	0.80
3/8	0.675	0.065	0.42	...	10	10	17.1	1.65	0.63
3/8	0.675	0.073	0.47	...	30	10	17.1	1.85	0.70
3/8	0.675	0.091	0.57	STD	40	10	17.1	2.31	0.84
3/8	0.675	0.126	0.74	XS	80	10	17.1	3.20	1.10
1/2	0.840	0.065	0.54	...	5	15	21.3	1.65	0.80
1/2	0.840	0.083	0.67	...	10	15	21.3	2.11	1.00
1/2	0.840	0.095	0.76	...	30	15	21.3	2.41	1.12
1/2	0.840	0.109	0.85	STD	40	15	21.3	2.77	1.27
1/2	0.840	0.147	1.09	XS	80	15	21.3	3.73	1.62
1/2	0.840	0.188	1.31	...	160	15	21.3	4.78	1.95
1/2	0.840	0.294	1.72	XXS	...	15	21.3	7.47	2.55
3/4	1.050	0.065	0.69	...	5	20	26.7	1.65	1.03
3/4	1.050	0.083	0.86	...	10	20	26.7	2.11	1.28
3/4	1.050	0.095	0.97	...	30	20	26.7	2.41	1.44
3/4	1.050	0.113	1.13	STD	40	20	26.7	2.87	1.69
3/4	1.050	0.154	1.48	XS	80	20	26.7	3.91	2.20
3/4	1.050	0.219	1.95	...	160	20	26.7	5.56	2.90
3/4	1.050	0.308	2.44	XXS	...	20	26.7	7.82	3.64
1	1.315	0.065	0.87	...	5	25	33.4	1.65	1.29
1	1.315	0.109	1.41	...	10	25	33.4	2.77	2.09
1	1.315	0.114	1.46	...	30	25	33.4	2.90	2.18
1	1.315	0.133	1.68	STD	40	25	33.4	3.38	2.50
1	1.315	0.179	2.17	XS	80	25	33.4	4.55	3.24
1	1.315	0.250	2.85	...	160	25	33.4	6.35	4.24
1	1.315	0.358	3.66	XXS	...	25	33.4	9.09	5.45
1 1/4	1.660	0.065	1.11	...	5	32	42.2	1.65	1.65
1 1/4	1.660	0.109	1.81	...	10	32	42.2	2.77	2.69
1 1/4	1.660	0.117	1.93	...	30	32	42.2	2.97	2.87
1 1/4	1.660	0.140	2.27	STD	40	32	42.2	3.56	3.39
1 1/4	1.660	0.191	3.00	XS	80	32	42.2	4.85	4.47
1 1/4	1.660	0.250	3.77	...	160	32	42.2	6.35	5.61
1 1/4	1.660	0.382	5.22	XXS	...	32	42.2	9.70	7.77
1 1/2	1.900	0.065	1.28	...	5	40	48.3	1.65	1.90
1 1/2	1.900	0.109	2.09	...	10	40	48.3	2.77	3.11
1 1/2	1.900	0.125	2.37	...	30	40	48.3	3.18	3.53
1 1/2	1.900	0.145	2.72	STD	40	40	48.3	3.68	4.05
1 1/2	1.900	0.200	3.63	XS	80	40	48.3	5.08	5.41
1 1/2	1.900	0.281	4.86	...	160	40	48.3	7.14	7.25
1 1/2	1.900	0.400	6.41	XXS	...	40	48.3	10.15	9.55