



# DETAILING MANUAL

## Zee Section Profile and Dimensions (Galvanized Coil)

Section : 5  
Page : 6.3  
Revision Date : 5-30-08  
Issue Date : 12-1-97  
Release No. : TIR.03.2008

Section Depth and Gauge	Depth "D" (in.)	Flange "B" (in.)	Lip "d" (in.)	Thick "T" (in.)	Weight (lbs./ft.)	Coil Width (in.)
4Z16	4.000	2.000	0.563	0.062	1.83	8.700
4Z14	4.000	2.000	0.563	0.077	2.28	
6Z16	6.000	2.000	0.563	0.062	2.26	10.700
6Z14	6.000	2.000	0.563	0.077	2.80	
8Z16	8.000	2.500	0.750	0.062	2.96	14.063
8Z15 <sup>1</sup>	8.000	2.500	0.750	0.069	3.30	
8Z14	8.000	2.500	0.750	0.077	3.68	
8Z13 <sup>1</sup>	8.000	2.500	0.750	0.091	4.35	
8Z12	8.000	2.500	0.750	0.101	4.83	
9.5Z15 <sup>1</sup>	9.500	3.000	0.875	0.069	3.93	16.750
9.5Z14	9.500	3.000	0.875	0.077	4.39	
9.5Z13 <sup>1</sup>	9.500	3.000	0.875	0.091	5.18	
9.5Z12	9.500	3.000	0.875	0.101	5.75	
12Z13 <sup>1</sup>	12.000	3.125	1.000	0.091	6.11	19.750
12Z12	12.000	3.125	1.000	0.101	6.78	

All Section Depths and gauges listed above are available in Galvanized except as noted.  
See page 6.2 for Red, Universal Red, Gray, Universal Gray and Bare availability.

Note:

1. Available at the Carson City, NV plant ONLY
2. All radii 1/4" U.N.

