

Joe Nimens 1 705 493 2760



HSD Drivers available for Rent or Lease

HSD Model	HSD 6-50	HSD 15-200
Max shaft dia.	6 inches	15 inches
Max torque (ft*lbs)	50,000	200,000
Max shaft length	upto 60 ft.	upto 100 ft.
Configuration	2 Speed	2 Speed
Production rate (Ft/min)	upto 10	upto 10
Weight of HSD unit	525 lbs.	3500 lbs
Carrier unit	Excavator	Excavator
Carrier weight	3 to 10 tons	20 to 50 tons
Wrench wrapping	Manual	Manual
Max crowding force	5,000 lbs.	40,000 lbs.





Joe Nimens 1 705 493 2760

Applications	Grouted helical Mini Piles	Pipe Pile 250X13mm Calsson 750mm/30"	Driven HP12X74 Calsson 900mm/36"	Driven HP14X101 Calsson 1.2m/48"	Shoring Tie Backs Vertical Anchors
HS Product	HS 400/16	HS 750/30	HS 900/36	HS 1200/48	HS 500/20
Load Capacity (Soil dependant)	100 Kips 444 KN	200 Kips 889 KN	300 Kips 1333 KN	400 Kips 1778 KN	150 Kips 667 KN
Length (Longer if spliced)	Up to 60 Feet Up to 18 m	Up to 60 Feet Up to 18 m	Upto 100 Feet Up to 30 m	Upto 100 Feet Up to 30 m	Up to 100 Feet Up to 30 m
Installation	10 minutes	10 minutes	20 minutes	20 minutes	15 minutes