

Pluggable interface relays

Ordering details



CR-M

2CDC 291 046 F0004

Description

Interface relays are widely used in various industrial applications:

As an interface they link the electronic controlling, e.g. PLC (programmable logic controller), PC or field bus systems, to the sensor / actuator level. Here, they take on various functions: Switching of AC or DC loads with different resistive, inductive and capacitive parts, switching voltages from a few mV up to 250 V, switching currents from a few mA up to 16 A, amplification of weak control signals, electrical isolation of control and load circuits, and signal multiplying. In contrast to electronic switching devices, interface relays don't use additional internal protective circuits and thus are overload-proof against short-time variations like current or voltage peaks.

Ordering details - CR-M range

Rated control supply voltage	Outputs	Contact ratings	Type	Order code	Price	Pkg qty	Weight (1 pce) kg (lb)
12 V DC	2 c/o (SPDT) without LED	250 V, 12 A	CR-M012DC2	1SVR405611R4000		10	0.033 (0.073)
24 V DC			CR-M024DC2	1SVR405611R1000			
48 V DC			CR-M048DC2	1SVR405611R6000			
60 V DC			CR-M060DC2	1SVR405611R4200			
110 V DC			CR-M110DC2	1SVR405611R8000			
125 V DC			CR-M125DC2	1SVR405611R8200			
220 V DC			CR-M220DC2	1SVR405611R9000			
24 V AC			CR-M024AC2	1SVR405611R0000			
48 V AC			CR-M048AC2	1SVR405611R5000			
110 V AC			CR-M110AC2	1SVR405611R7000			
120 V AC			CR-M120AC2	1SVR405611R2000			
230 V AC			CR-M230AC2	1SVR405611R3000			
12 V DC	3 c/o (SPDT) without LED	250 V, 10 A	CR-M012DC3	1SVR405612R4000		10	0.033 (0.073)
24 V DC			CR-M024DC3	1SVR405612R1000			
48 V DC			CR-M048DC3	1SVR405612R6000			
60 V DC			CR-M060DC3	1SVR405612R4200			
110 V DC			CR-M110DC3	1SVR405612R8000			
125 V DC			CR-M125DC3	1SVR405612R8200			
220 V DC			CR-M220DC3	1SVR405612R9000			
24 V AC			CR-M024AC3	1SVR405612R0000			
48 V AC			CR-M048AC3	1SVR405612R5000			
			CR-M060AC3	1SVR405612R5200			
110 V AC			CR-M110AC3	1SVR405612R7000			
120 V AC			CR-M120AC3	1SVR405612R2000			
230 V AC			CR-M230AC3	1SVR405612R3000			
12 V DC	4 c/o (SPDT) without LED	250 V, 6 A	CR-M012DC4	1SVR405613R4000		10	0.033 (0.073)
24 V DC			CR-M024DC4	1SVR405613R1000			
48 V DC			CR-M048DC4	1SVR405613R6000			
60 V DC			CR-M060DC4	1SVR405613R4200			
110 V DC			CR-M110DC4	1SVR405613R8000			
125 V DC			CR-M125DC4	1SVR405613R8200			
220 V DC			CR-M220DC4	1SVR405613R9000			
24 V AC			CR-M024AC4	1SVR405613R0000			
48 V AC			CR-M048AC4	1SVR405613R5000			
110 V AC			CR-M110AC4	1SVR405613R7000			
120 V AC			CR-M120AC4	1SVR405613R2000			
230 V AC			CR-M230AC4	1SVR405613R3000			

Bold printed products = stocked products

Pluggable interface relays

Ordering details



CR-M

2CDC 291 046 F0004

5

Ordering details - CR-M range							
Rated control supply voltage	Outputs	Contact ratings	Type	Order code	Price	Pkg qty	Weight (1 pce) kg (lb)
12 V DC	2 c/o (SPDT) with LED	250 V, 12 A	CR-M012DC2L	1SVR405611R4100		10	0.033 (0.073)
24 V DC			CR-M024DC2L	1SVR405611R1100			
48 V DC			CR-M048DC2L	1SVR405611R6100			
60 V DC			CR-M060DC2L	1SVR405611R4300			
110 V DC			CR-M110DC2L	1SVR405611R8100			
125 V DC			CR-M125DC2L	1SVR405611R8300			
220 V DC			CR-M220DC2L	1SVR405611R9100			
24 V AC			CR-M024AC2L	1SVR405611R0100			
48 V AC			CR-M048AC2L	1SVR405611R5100			
110 V AC			CR-M110AC2L	1SVR405611R7100			
120 V AC			CR-M120AC2L	1SVR405611R2100			
230 V AC			CR-M230AC2L	1SVR405611R3100			
12 V DC	3 c/o (SPDT) with LED	250 V, 10 A	CR-M012DC3L	1SVR405612R4100		10	0.033 (0.073)
24 V DC			CR-M024DC3L	1SVR405612R1100			
48 V DC			CR-M048DC3L	1SVR405612R6100			
60 V DC			CR-M060DC3L	1SVR405612R4300			
110 V DC			CR-M110DC3L	1SVR405612R8100			
125 V DC			CR-M125DC3L	1SVR405612R8300			
220 V DC			CR-M220DC3L	1SVR405612R9100			
24 V AC			CR-M024AC3L	1SVR405612R0100			
48 V AC			CR-M048AC3L	1SVR405612R5100			
110 V AC			CR-M110AC3L	1SVR405612R7100			
120 V AC			CR-M120AC3L	1SVR405612R2100			
230 V AC			CR-M230AC3L	1SVR405612R3100			
12 V DC	4 c/o (SPDT) with LED	250 V, 6 A	CR-M012DC4L	1SVR405613R4100		10	0.033 (0.073)
24 V DC			CR-M024DC4L	1SVR405613R1100			
48 V DC			CR-M048DC4L	1SVR405613R6100			
60 V DC			CR-M060DC4L	1SVR405613R4300			
110 V DC			CR-M110DC4L	1SVR405613R8100			
125 V DC			CR-M125DC4L	1SVR405613R8300			
220 V DC			CR-M220DC4L	1SVR405613R9100			
24 V AC			CR-M024AC4L	1SVR405613R0100			
48 V AC			CR-M048AC4L	1SVR405613R5100			
110 V AC			CR-M110AC4L	1SVR405613R7100			
120 V AC			CR-M120AC4L	1SVR405613R2100			
230 V AC2			CR-M230AC4L	1SVR405613R3100			
24 V DC	4 c/o (SPDT) LED and free-wheeling diode	250 V, 6 A	CR-M024DC4LD	1SVR405614R1100		10	0.033 (0.073)
24 V DC	4 (SPDT) c/o gold contacts	250 V, 6 A	CR-M024DC4G	1SVR405618R1000		10	0.033 (0.073)
24 V AC			CR-M024AC4G	1SVR405618R0000			
110 V AC			CR-M110AC4G	1SVR405618R7000			
230 V AC			CR-M230AC4G	1SVR405618R3000			

Bold printed products = stocked products

Pluggable interface relays

Ordering details



CR-M

2CDC 291 048 F0004

Rated control supply voltage	Outputs	Contact ratings	Type	Order code	Price	Pkg qty	Weight (1 pce) kg (lb)
12 V DC	4 c/o (SPDT) with gold contacts and LED	250 V / 6 A	CR-M012DC4LG	1SVR405618R4100		10	0.033 (0.073)
24 V DC			CR-M024DC4LG	1SVR405618R1100			
48 V DC			CR-M048DC4LG	1SVR405618R6100			
60 V DC			CR-M060DC4LG	1SVR405618R4300			
110 V DC			CR-M110DC4LG	1SVR405618R8100			
125 V DC			CR-M125DC4LG	1SVR405618R8300			
220 V DC			CR-M220DC4LG	1SVR405618R9100			
24 V AC			CR-M024AC4LG	1SVR405618R0100		10	0.033 (0.073)
48 V AC			CR-M048AC4LG	1SVR405618R5100			
110 V AC			CR-M110AC4LG	1SVR405618R7100			
120 V AC			CR-M120AC4LG	1SVR405618R2100			
230 V AC			CR-M230AC4LG	1SVR405618R3100			
12 V DC	4 c/o (SPDT) with gold contacts, LED and free-wheeling diode		CR-M012DC4LDG	1SVR405618R4400		10	0.033 (0.073)
24 V DC			CR-M024DC4LDG	1SVR405618R1400			



CR-M4SS

2CDC 291 009 R0011



CR-MJ

Ordering details - Accessories

Version	Connection terminal	Type	Order code	Price	Pkg qty	Weight (1 pce) kg (lb)
Logical socket for 2 c/o	screw	CR-M2LS	1SVR405651R1100		10	0.055 (0.121)
Logical socket for 3 c/o		CR-M3LS	1SVR405651R2100			0.062 (0.137)
Logical socket for 2/4 c/o		CR-M4LS	1SVR405651R3100			0.066 (0.146)
Logical socket for 2 c/o	spring	CR-M2LC	1SVR405651R1200		10	0.065 (0.143)
Logical socket for 2/4 c/o		CR-M4LC	1SVR405651R3200			0.066 (0.146)
Standard socket for 2 c/o	screw	CR-M2SS	1SVR405651R1000		10	0.066 (0.146)
Standard socket for 3 c/o		CR-M3SS	1SVR405651R2000			0.068 (0.150)
Standard socket for 2/4 c/o		CR-M4SS	1SVR405651R3000			0.070 (0.154)
Standard socket for 2 c/o	fork type	CR-M2SF	1SVR405651R1300		10	0.040 (0.088)
Standard socket for 2/4 c/o		CR-M4SF	1SVR405651R3300			0.048 (0.106)
Plastic holder		CR-MH	1SVR405659R1000		10	0.003 (0.007)
Metal holder		CR-MH1	1SVR405659R1100		25	0.0005 (0.001)
CR-MJ		CR-MJ	1SVR405658R6000		10	0.029 (0.064)
CR-M		CR-MM	1SVR405658R1000		10	0.0005 (0.001)


Bold printed products = stocked products

Pluggable interface relays


Technical data

Input circuit - coil data


CR-P range

	Rated control supply voltage U_s	Rated frequency	Make voltage (at 20 °C)	Maximum voltage (at 55 °C)	Break voltage	Rated power	Coil resistance (at 20 °C)	Tolerance of coil resistance
DC coils	12 V DC	-	8.4 V DC	30.6 V DC	$\geq 0.1 U_s$	0.4-0.48 W	360 Ω	$\pm 10\%$
	24 V DC	-	16.8 V DC	61.2 V DC	$\geq 0.1 U_s$	0.4-0.48 W	1440 Ω	$\pm 10\%$
	48 V DC	-	33.6 V DC	122.4 V DC	$\geq 0.1 U_s$	0.4-0.48 W	5700 Ω	$\pm 10\%$
	110 V DC	-	77 V DC	280 V DC	$\geq 0.1 U_s$	0.4-0.48 W	25200 Ω	$\pm 10\%$
AC coils	24 V AC	50 / 60 Hz	19.2 V AC	28.8 V AC	$\geq 0.15 U_s$	0.75 VA	400 Ω	$\pm 10\%$
	48 V AC	50 / 60 Hz	38.4 V AC	57.6 V AC	$\geq 0.15 U_s$	0.75 VA	1550 Ω	$\pm 10\%$
	110 V AC	50 / 60 Hz	88 V AC	132 V AC	$\geq 0.15 U_s$	0.75 VA	8900 Ω	$\pm 10\%$
	120 V AC	50 / 60 Hz	96 V AC	144 V AC	$\geq 0.15 U_s$	0.75 VA	10200 Ω	$\pm 10\%$
	230 V AC	50 / 60 Hz	184 V AC	276 V AC	$\geq 0.15 U_s$	0.75 VA	38500 Ω	$\pm 10\%$

CR-M range

	Rated control supply voltage U_s	Rated frequency	Make voltage (at 20 °C)	Maximum voltage (at 55 °C)	Break voltage	Rated power	Coil resistance (at 20 °C)	Tolerance of coil resistance
DC coils	12 V DC	-	9.6 V DC	13.2 V DC	$\geq 0.1 U_s$	0.9 W	160 Ω	$\pm 10\%$
	24 V DC	-	19.2 DC	26.4 V DC	$\geq 0.1 U_s$	0.9 W	640 Ω	$\pm 10\%$
	48 V DC	-	38.4 V DC	52.8 V DC	$\geq 0.1 U_s$	0.9 W	2600 Ω	$\pm 10\%$
	60 V DC	-	48.0 V DC	66.0 V DC	$\geq 0.1 U_s$	0.9 W	4000 Ω	$\pm 10\%$
	110 V DC	-	88 V DC	121 V DC	$\geq 0.1 U_s$	0.9 W	13600 Ω	$\pm 10\%$
	125 V DC	-	100 V DC	137.5 V DC	$\geq 0.1 U_s$	0.9 W	16000 Ω	$\pm 10\%$
	220 V DC	-	176 V DC	242 V DC	$\geq 0.1 U_s$	0.9 W	54000 Ω	$\pm 10\%$
AC coils	24 V AC	50 / 60 Hz	19.2 V AC	26.4 V AC	$\geq 0.2 U_s$	1.6 VA	158 Ω	$\pm 10\%$
	48 V AC	50 / 60 Hz	38.4 V AC	52.8 V AC	$\geq 0.2 U_s$	1.6 VA	640 Ω	$\pm 10\%$
	60 V AC	50 / 60 Hz	48.0 V AC	66.0 V AC	$\geq 0.2 U_s$	1.6 VA	930 Ω	$\pm 10\%$
	110 V AC	50 / 60 Hz	88 V AC	121 V AC	$\geq 0.2 U_s$	1.6 VA	3450 Ω	$\pm 10\%$
	120 V AC	50 / 60 Hz	96 V AC	132 V AC	$\geq 0.2 U_s$	1.6 VA	3770 Ω	$\pm 10\%$
	230 V AC	50 / 60 Hz	184 V AC	253 V AC	$\geq 0.2 U_s$	1.6 VA	16100 Ω	$\pm 10\%$

CR-U range

	Rated control supply voltage U_s	Rated frequency	Make voltage (at 20 °C)	Maximum voltage (at 55 °C)	Break voltage	Rated power	Coil resistance (at 20 °C)	Tolerance of coil resistance
DC coils	12 V DC	-	9.6 V DC	13.2 V DC	$\geq 0.1 U_s$	1.5 W	110 Ω	$\pm 10\%$
	24 V DC	-	19.2 V DC	26.4 V DC	$\geq 0.1 U_s$	1.5 W	430 Ω	$\pm 10\%$
	48 V DC	-	38.4 V DC	52.8 V DC	$\geq 0.1 U_s$	1.5 W	1750 Ω	$\pm 10\%$
	110 V DC	-	88.0 V DC	121.0 V DC	$\geq 0.1 U_s$	1.5 W	9200 Ω	$\pm 10\%$
	125 V DC	-	96.0 V DC	132.0 V DC	$\geq 0.1 U_s$	1.5 W	11000 Ω	$\pm 10\%$
	220 V DC	-	176.0 V DC	242.0 V DC	$\geq 0.1 U_s$	1.5 W	37000 Ω	$\pm 10\%$
AC coils	24 V AC	50 / 60 Hz	19.2 V AC	26.4 V AC	$\geq 0.15 U_s$	2.8 VA (50 Hz) 2.5 VA (60 Hz)	75 Ω	$\pm 10\%$
	48 V AC	50 / 60 Hz	38.4 V AC	52.8 V AC	$\geq 0.15 U_s$	2.8 VA (50 Hz) 2.5 VA (60 Hz)	305 Ω	$\pm 10\%$
	60 V AC	50 / 60 Hz	48.0 V AC	66.0 V AC	$\geq 0.15 U_s$	2.8 VA (50 Hz) 2.5 VA (60 Hz)	475 Ω	$\pm 10\%$
	110 V AC	50 / 60 Hz	88.0 V AC	121.0 V AC	$\geq 0.15 U_s$	2.8 VA (50 Hz) 2.5 VA (60 Hz)	1700 Ω	$\pm 10\%$
	120 V AC	50 / 60 Hz	96.0 V AC	132.0 V AC	$\geq 0.15 U_s$	2.8 VA (50 Hz) 2.5 VA (60 Hz)	1910 Ω	$\pm 10\%$
	230 V AC	50 / 60 Hz	184.0 V AC	253.0 V AC	$\geq 0.15 U_s$	2.8 VA (50 Hz) 2.5 VA (60 Hz)	7080 Ω	$\pm 10\%$

Pluggable interface relays

Technical data

5

Type		CR-P...1	CR-P...2	CR-M...2	CR-M...3	CR-M...4	CR-U...2	CR-U...3
Output circuit(s)		11-12/14	11-12/14 21-22/24	11-12/14 21-22/24	11-12/14 21-22/24 31-32/34	11-12/14 21-22/24 31-32/34 41-42/44	11-12/14 31-32/34	11-12/14 21-22/24 31-32/34
Kind of output		Relay, 1 c/o	Relay, 2 c/o	Relay, 2 c/o	Relay, 3 c/o	Relay, 4 c/o	Relay, 2 c/o	Relay, 3 c/o
Contact material		AgNi	AgNi AgNi/Au 5 µm	AgNi	AgNi	AgNi AgNi/Au 5 µm	AgNi	
Rated operational voltage U _e (VDE 0110, IEC 60947-1)		250 V						
Minimum switching voltage		5 V						
Maximum switching voltage	DC	300 V DC			250 V DC			
	AC	400 V AC			250 V AC			
Minimum switching current		5 mA (AgNi), 2 mA (AgNi/Au)						
Rated free air thermal current I _{th}		16 A	8 A	12 A	10 A	6 A	10 A	
Rated operational current (IEC 60947-5-1)	AC12 (resistive) 230 V	16 A	8 A	12 A	10 A	6 A	10 A	
	AC15 (inductive) 230 V	1.5 A	1 A	1.5 A	1.5 A	1 A	1.5 A	
	DC12 (resistive) 24 V	16 A	8 A	12 A	10 A	6 A	10 A	
	DC13 (inductive) 24 V	2 A	2 A	8 A	8 A	6 A	2 A	
AC rating (UL 508)	Utilization category (Control Circuit Rating Code)	-		-			-	B 300
	max. rated operational voltage	-		-			-	300 V AC
	max. continuous thermal current at B 300	-		-			-	5 A
	max. making / breaking apparent power at B 300	-		-			-	3600/360 VA
	Utilization category General Purpose (single phase)	-		-			10 A, 250 V AC	10 A, 250 V AC
	Utilization category (Resistive)	16 A, 250 V AC	8 A, 250 V AC	10 A, 250 V AC 12 A, 150 V AC	6 A, 250 V AC 10 A, 150 V AC	6 A, 250 V AC 10 A, 150 V AC	10 A, 250 V AC	-
	Minimum switching power	0.3 W (AgNi), 0.1 W (AgNi/Au)						
Maximum switching power	AC-1	4000 VA	2000 VA	3000 VA	2500 VA	1500 VA	2500 VA	
Contact resistance		≤ 100 mΩ			≤ 100 mΩ			
Maximum switching capacity	rated load AC-1	600 switching cycles/h			1200 switching cycles/h			
	without load	72000 switching cycles/h			18000 switching cycles/h		12000 switching cycles/h	
Mechanical lifetime		> 3 x 10 ⁷ switching cycles			> 2 x 10 ⁷ switching cycles			
Electrical lifetime	AC1 (resistive)	> 10 ⁵ switching cycles (16 A, 250 V) (8 A, 250 V)			> 10 ⁵ switching cycles (12 A, 250 V) (10 A, 250 V) (6 A, 250 V)			> 10 ⁵ switching cycles (10 A, 250 V)
	cos φ	see reduction factor F						
Response time		typ. 7 ms			typ. 13 ms (DC), 10 ms (AC)		typ. 18 ms (DC), 12 ms (AC)	
Release time		typ. 3 ms			typ. 3 ms (DC), 8 ms (AC)		typ. 7 ms (DC), 10 ms (AC)	
Isolation data								
Rated insulation voltage		400 V AC			250 V AC			
Insulation class		C250 / B400			C250 / B250		C250	
Rated impulse withstand voltage U _{imp}	between coil and contacts	5 kV AC			2.5 kV AC			
	between open contacts	1 kV AC			1.5 kV AC			
	between c/o contacts	2.5 kV AC			2.5 kV AC	2 kV AC	2 kV AC	
Clearance	between coil and contacts	≥ 10 mm			≥ 2.5 mm	≥ 1.6 mm	≥ 3 mm	
Creepage distance	between coil and contacts	≥ 10 mm			≥ 4 mm	≥ 3.2 mm	≥ 4.2 mm	
Overvoltage category		III			III	II	III	
Pollution degree		3			3	2	3	
General data								
Dimensions (W x H x D) when mounted		12.7 x 29 x 15.7 mm			21.2 x 27.5 x 35.6 mm		35 x 35 x 54.4 mm	
Weight		14 g (0.031 lb)			35 g (0.077 lb)		83 g (0.18 lb)	
Mounting		on socket (see accessories)						
Mounting position		any						
Degree of protection		IP 67			IP 40			
Electrical connection								
Connection		by socket						