

**NOTES, UNLESS OTHERWISE SPECIFIED:**

1. CABLE/WIRE HARNESS TO BE TESTED 100% FOR POLARITY AND CONTINUITY.
2. REFER TO CONNECTOR INSTALLATION INSTRUCTIONS FOR COMPLETE ASSEMBLY.
3. CONNECTOR: MOLEX MIZU-P25 52117-0410.
4. CABLE SPECIFICATION: TYPE UL3266 24/19 XLPE, 24AW.
  1. MINIMUM RATING: >=105°C MINIMUM, 300V MINIMUM
  2. CONDUCTOR INSULATION COLORS:
    1. BLACK
    2. RED
    3. YELLOW
    4. BROWN
    5. GREEN
    6. ORANGE
5. CONNECTOR PIN POSITIONS:
  3. PIN 1: BLACK
  4. PIN 2: RED
  5. PIN 3: YELLOW
  6. PIN 4: BROWN
6. PARTS TO BE CLEAN AND MUST BE FREE OF ANY OILS OR CONTAMINANTS.
7. ITEM BALLONS SHOWN ON SHEETS OF THIS DRAWING ARE FOR USE WITH BOM ON THIS SHEET.
8. BOM SHOWN FOR REFERENCE ONLY, REFER TO BOM DATABASE (MRP) FOR CURRENT DATA.
9. SUPPLIER MAY NOT MAKE ANY CHANGES IN MATERIAL SOURCES, MATERIAL COMPOSITION, OR MAKE MODIFICATIONS TO PROCESSES THAT IN ANY WAY AFFECT PART PROPERTIES WITHOUT WRITTEN APPROVAL FROM LSGC.
10. CERTIFICATE OF CONFORMANCE (COC) SHALL BE SUPPLIED TO LSGC FOR EACH PURCHASE ORDER.
11. COC MUST INCLUDE LSGC DRAWING NUMBER, AND REVISION LEVEL.
12. BAG AND LABEL WITH LSGC PART NUMBER, LATEST REVISION, AND P.O. NUMBER.

