

RELTON CORPORATION



CARBIDE-TIPPED ROTARY REBAR CUTTER



Made in U.S.A.

SRB-11

CARBIDE-TIPPED ROTARY-ONLY REBAR CUTTERS

At last, the answer to drilling through concrete-embedded rebar! No more broken or shattered hammer bits; now you can drill through the rebar and not have to relocate the hole to avoid the rebar!

**STRAIGHT
SHANK**

**SDS+
SHANK**

DIA	OVERALL LENGTH	Straight-Shank		SDS+		WT. (lbs)	SUGGESTED RPM'S	PIECES
		PART NO.	LIST PRICE	PART NO.	LIST PRICE			
3/8"	8"	RB-6	\$ 52.00	SRB-6	\$ 54.00	0.3	850-1200	This is a one-piece system (shanks are non-removable).
3/8"	12"	RB-6-12	68.00	SRB-6-12	70.00	0.3	850-1200	
3/8"	12"	RB-6-18	80.00	SRB-6-18	82.00	0.5	850-1200	
7/16"	12"	RB-7	62.00	SRB-7	64.00	0.5	850-1200	
1/2"	12"	RB-8	54.00	SRB-8	56.00	0.6	850-1200	
1/2"	18"	RB-8-18	81.00	SRB-8-18	83.00	1.0	850-1200	
9/16"	12"	RB-9	62.00	SRB-9	64.00	0.7	850-1200	
9/16"	12"	RB-9-18	85.00	SRB-9-18	87.00	1.1	850-1200	
5/8"	12"	RB-10	65.00	SRB-10	67.00	0.8	750-1000	
5/8"	18"	RB-10-18	87.00	SRB-10-18	89.00	1.3	750-1000	
11/16"	12"	RB-11	74.00	SRB-11	76.00	0.9	750-1000	
3/4"	12"	RB-12	75.00	SRB-12	77.00	1.1	600-850	This is a two-piece system, and comes with a shank to make a overall length of 12"; however, longer or shorter shanks are avail- able...see shanks below
3/4"	18"	RB-12-18	96.00	SRB-12-18	98.00	1.6	600-850	
3/4"	24"	RB-12-24	110.00	SRB-12-24	112.00	1.8	600-850	
13/16"	12"	RB-13	81.00	SRB-13	83.00	1.1	600-850	
7/8"	12"	RB-14	100.00	SRB-14	103.00	0.9	600-850	
1"	12"	RB-16	104.00	SRB-16	107.00	1.1	500-750	
1 1/8"	12"	RB-18	123.00	SRB-18	126.00	1.2	500-750	
1 1/4"	12"	RB-20	130.00	SRB-20	133.00	1.3	450-600	
1 3/8"	12"	RB-22	132.00	SRB-22	135.00	1.4	450-600	
1 1/2"	12"	RB-24	145.00	SRB-24	148.00	1.6	350-500	
1 5/8"	12"	RB-26	178.00	SRB-26	181.00	1.7	350-500	
1 3/4"	12"	RB-28	183.00	SRB-28	186.00	1.8	350-500	
2"	12"	RB-32	202.00	SRB-32	205.00	2.5	350-500	
2 1/2"	12"	RB-40	220.00	SRB-40	223.00	3.1	350-500	



REPLACEMENT SHANKS 7/8" & LARGER

REPLACEMENT CUTTER HEAD 7/8" & LARGER



STRAIGHT SHANK


SDS+ SHANK

	PART NO.	LIST PRICE	SHANK	TO MAKE OAL BIT LENGTH	WT. (lbs)	THREAD SIZE	DIA	PART NO.	LIST PRICE	WT. (lbs)	SUGGESTED RPM'S	THREAD SIZE
NEW NEW NEW NEW	TDS-2-9	\$12.00	1/2"	9"	0.4	1/2-13 MALE	7/8"	RB-14HO	\$ 86.00	0.4	600-850	1/2-13 FEMALE
	TDS-2-12	14.00	1/2"	12"	0.5		1"	RB-16HO	90.00	0.6	500-750	
	TDS-2-18	21.00	1/2"	18"	0.9		1 1/8"	RB-18HO	109.00	0.7	500-750	
	TDS-2-24	29.00	1/2"	24"	1.2		1 1/4"	RB-20HO	116.00	0.8	450-600	
	STDS-2-9	14.00	SDS	9"	0.4		1 3/8"	RB-22HO	118.00	0.9	450-600	
	STDS-2-12	17.00	SDS	12"	0.5		1 1/2"	RB-24HO	131.00	1.1	350-500	
	STDS-2-18	23.00	SDS	18"	0.9		1 5/8"	RB-26HO	164.00	1.2	350-500	
	STDS-2-24	31.00	SDS	24"	1.2		1 3/4"	RB-28HO	169.00	1.3	350-500	
NEW NEW NEW NEW	TDS-3-9	12.00	1/2"	9"	0.4	3/4-10 MALE	2"	RB-32HO	188.00	1.8	350-500	3/4-10 FEMALE
	TDS-3-12	14.00	1/2"	12"	0.5							
	TDS-3-18	21.00	1/2"	18"	0.9							
	TDS-3-24	29.00	1/2"	24"	1.2							
	STDS-3-9	14.00	SDS	9"	0.4		2 1/2"	RB-40HO	206.00	2.4	350-500	
	STDS-3-12	17.00	SDS	12"	0.5							
	STDS-3-18	23.00	SDS	18"	0.9							
	STDS-3-24	31.00	SDS	24"	1.2							

Follow power tool manufacturers' recommendations for bit capacity.

EASY AS....

- When rebar is encountered while drilling with a rotary hammer and a carbide hammer bit, immediately stop the hammer and remove the bit from the hole (failure to stop could severely damage a carbide hammer bit - regardless of manufacturer's claim).
- Mount a rotary rebar cutter in a standard 1/2" chuck/drill motor or SDS+ rotary hammer-motor (with the selector in the **rotary-only position**); insert the rotary rebar cutter into the hole and drill through the embedded rebar.
- Remove the rotary rebar cutter after the rebar has been drilled completely through and finish drilling the hole with the rotary hammer and hammer bit.



NOTICE:

The Relton carbide-tipped rotary rebar cutter is designed for use in a standard 1/2" chuck/drill motor or SDS+ hammer motor provided the selector mechanism is kept in the **rotary-only position**.

The Relton carbide-tipped rotary rebar cutter is intended for **rotary** drilling only; percussion (hammering action) will damage the tool.

SAFETY NOTE: The operator of this tool assumes sole responsibility for any adverse structural effects of cutting rebar. Consult structural engineers if you have any concerns.

Distributed By



RELTON
CORPORATION



317 ROLYN PLACE, ARCADIA, CALIFORNIA 91007-2838 (800) 423-1505 Fax (626) 446-9671 <http://www.relton.com>

SRB-11