



NOTE:
1) ALL DOWEL LOCATIONS TO
BE $\pm .0005$ UNLESS
OTHERWISE SPECIFIED

QUANTITY REQ'D		DESCRIPTION										
<div>STANDARD NOTES <u>UNLESS OTHERWISE SPECIFIED</u> 1) STAMP "JOB, STA, DET, AND MAT'L" 2) BREAK ALL SHARP EDGES 1/32" 3) GROUND DIAMETERS CONCENTRIC WITHIN .0005" 4) HOLE LOCATIONS (X.XXX) TO BE +/- .005 UNLESS OTHERWISE SPECIFIED</div>		3RD STA DIE HOLDER BLOCK										
		<div>INCH TOLERANCES <u>UNLESS OTHERWISE SPECIFIED</u></div> <table><tr><td colspan="2">DECIMALS</td><td>THREAD DEPTHS +/- .030"</td></tr><tr><td>.XX</td><td>+/- .010"</td><td>ANGLES +/- 0.5°</td></tr><tr><td>.XXX</td><td>+/- .001"</td><td>FRAC. +/- 1/32"</td></tr><tr><td>.XXXX</td><td>+/- .0005"</td><td>INSIDE RADII .015" MAX</td></tr></table>	DECIMALS		THREAD DEPTHS +/- .030"	.XX	+/- .010"	ANGLES +/- 0.5°	.XXX	+/- .001"	FRAC. +/- 1/32"	.XXXX
DECIMALS		THREAD DEPTHS +/- .030"										
.XX	+/- .010"	ANGLES +/- 0.5°										
.XXX	+/- .001"	FRAC. +/- 1/32"										
.XXXX	+/- .0005"	INSIDE RADII .015" MAX										

REV. 4/23/08