

File Shopping carts Administration SAP maintain Help...
 Version 10.8 build Release (02.08.2011) Guest KSB (ANONYMOUS) 1469789 YA Version: 1
 KSB EasySelect Units of quantity English Contact finder KSB EasySelect Version 5.0c
 << Back Start Selection Configuration Output Price sheet Cancel Next >>

Solutions
 KSB recommendation Alternatives Performance curves

Select

Sewatec / Sewabloc K K 050-251

Flow rate	300.00 US GPM
Discharge head	230.00 ft
Efficiency	56.3 %
Speed of rotation	2925 rpm
Power absorbed	31.30 HP
NPSH req.	26.74 ft
Prices from	on req.
Number of stages	1
Free passage	0.59 in
Impeller diameter	10.08 in

Max. disch. press.: 145.038 psi.a

Sewabloc **Sewatec**

Information on important symbols

configuration:

get an explanation

to restore the default
can "fix" a value directly by

the online help for them.

Next >>

Next and "Back" buttons. Use these two

navigation buttons with this
on itself.

Recommended browser settings

Close window

This is a solution suggested for your application. You can configure it by clicking on "Select" or "Next". More products are available under "Alternatives". Please verify the suitability of the suggested solution and alternatives taking into account the project-specific requirements of your application.