

ING

SHEATH ONE SIDE OF TRUSS OVER SHEARWALL W/ MIN. 3/8" A.P.A. RATED SHTG. W/ 8d NAILS @ 4" O/C @ ALL WEBS AND CHORDS OR DESIGN TRUSS FOR DRAG LOAD SHOWN ON PLAN

LS

12" O.C.

LER

16d NAILS @ 4" O.C.

2x12 MAX.

9" MAX

16d NAILS @ 4" O.C. STAGGERED

DBL. 2x TOP PLATE CONT.-TYP.

2x WOOD STUDS

SHEARWALL PER PLAN

INTERIOR BEARING WALL

- STRAP PATIO BEAM TO TOP PLATE OF THIS WALL

DS

ER PLAN

8d NAILS @ 6" O.C.

ROOF SHEATHING

ROOF TRUSSES

1 OF

2

8d NAILS @ 6" O.C.

ROOF SHEATHING

ROOF TRUSSES

8d NAILS @ 6" O.C.

2 OF

2

DESIGN TRUSS FOR DRAG LOAD SHOWN ON PLAN *

8d @ 4" O.C. STAGGERED

2x4 LEDGER NAILED TO BTM. CHORD W/ 16d @ 8" O.C.

8d @ 6" O.C.

MIN. 3/8" A.P.A. SHTG. CONT. OVER SHEARWALL

8d @ 6" O.C.

DBL. 2x TOP PLATE CONT.-TYP.

2x STUDS @ 16" O/C

SHEARWALL PER PLAN

SEE COMMENTS ON 1

*IF DRAG LOAD NOT INDICATED DESIGN FOR 2000 LBS