



API FLUID	S1	ACCEPTED USE
FLUSH FLUID	COOLANT	
FLUSH PRESS.	100 PSI	
FLUSH TEMP.	40°C	
FLUSH RATE	2-8 LPM	20-25 LPM

FLUID	K2DCSA/SLURRY
SUCTION PRESSURE	***
DISCHARGE PRESSURE	***
BOX PRESSURE	35.2 KG/SQCM
VAPOUR PRESSURE	***
TEMPERATURE	200°C
SPECIFIC GRAVITY	***
VISCOSITY	***
IPM	96

P.N.O.	DESCRIPTION	MATERIAL	PART CODE	QTY.
1	CLAND RING			
45	COMPRESSION UNIT			
* 2	INSERT			
* 3A	SEAL RING			
* 3	SEAL RING			
4	SHROUD			
5	COLLAR			
OP	GRIPUP			
* R2	CAP SCREW			
* 7	INSERT MTC.			
6	INSERT MTC.			
80	SHROUD DISC ASSY			
10	SLEEVE			
* 11	SLEEVE PACKING			
* 11A	SLEEVE PACKING			
* M4	O-RING			
* G	SPIRAL WOUND GASKET			
15	EOG WASHER			
16	INSERT HOLDER			
BP	BACK UP PLATE			
* K1	CAP SCREW			
* C	SPRING			
* D	DRIVE PIN			
* K	CAP SCREW			
G2	GASKET			
* O1	SHIRT PACKING			
* P1	SHIRT PACKING			
* H	HOOD RING			
* S	SET SCREWS			
* S1	DOG PT SETSCREW			
D1	DRIVE PIN			
A1	HOUSING			
B1	BEARING HOUSING			
* 14	COVER PLATE			
K3	KEY			
* B2	BEARING 22224D			
OS	OIL SEAL			
M	BOLT			
M1	GREASE NIPPLE			
M2	EYE BOLTS			
* M3	WASHER			
K3	CAPSCREW			
* H1	HEAT TRAP			
P	SHIRT PACKING			