EB-LINK

BL-MP01

Wireless Pocket Router



In home network, it occupies little space and saves power. All wireless devices can be connected.
Wireline device also can be upgraded to wireless device.
In hotel network, it can help you to allow multi-user sharing wireless network without cable

In hotel network, it can help you to allow multi-user snaring wireless network winnow concerestraint
In office network, you are free from pulling cable as it can bridge to any access point.
Outdoor, it acts as the receiver with high performance of wireless hot spot, allows multi-user sharing one ID account freely at the same time.
At the place where wireless signal is weak, it can enhance signal strength to extend the transmission distance,



LB-LINK®

With global extra small size, it works as a Mini WIFI signal amplifier, functions of AP, wireless LAN card, client all in one; It is the perfect match for Apple IPHONE and IPAD, as well as a good helper for mobile working; it is portable wireless product customized for business persons.



Product features

- Random choice of switching any mode among router, client and AP
- Supports WPS that encrypt by press one key, no need to set password.
- Plug and play, it's convenient to access wireless and share Internet
- Built in a device that can scan wireless hot spots, memorise SSID name and bridge, relay automatically, convenience to use.
- Supports users' behavior management, QOS advanced management, MAC address filtering, web page filtering and NAT address switching.
- Flexible multiple power way such as AC and USB charging, power adapter is configured randomly with this device(5V/500MA)
- High-Integrate and multifunction designs, compact body, easy to carry.

Product Specifications

Protocol and standard	IEEE 802.11b、IEEE 802.11g、 IEEE802.11n、 IEEE 802.3、 IEEE 802.3U;
Wireless signal transmission rate	11n:supports 150Mbps at most 11g:supports 54Mbps at most 11b:supports 11Mbps at most
Frequency range	2.4-2.4835GHz
Transmitting power	12~15dBm
Modulation technique	DBPSK, DQPSK, CCK, OFDM, 16-QAM, 64-QAM
Ports	RJ45 interface, USB interface
Antenna	built-in intelligent Omni-directional antenna
Button	Reset/WPS button
Power Adapter	DC 5V/500MA
Operating environment	Operating temperature : 0°C- 40°C; Storage temperature : -40°C-70°C; Working humidity : 10% -90% RH non-condensation; Storage temperature : 5% -90% RH non-condensation;

Package Size



ADD: B-LINK ELECTRONIC FACTORY, GUANLAN TOWN, SHENZHEN, CHINA TEL:0086-755-28023440 FAX:0086-755-28029002 Website:www.lefen.com