

STEEL PANEL FASTENED w/ SCREWS
NEXT TO EVERY RIB @ EACH PURLIN

2x4 PURLINS
SEE PAGE 6 FOR SPACING

RIPPED 2x6 PURLIN/NAILER w/
CHAMFER @ TOP & BOTTOM

12
4

1 1/2" HEEL TRUSS

RIPPED 2x6 END PURLIN
w/ CHAMFER @ TOP

NOTCH TRUSS INTO ONE PLY
OF COLUMN: SECURE TOP &
BOTTOM CHORDS w/ 5-20d
NAILS EACH

① 4-PLY 2x6 COLUMN

② 2x4 SPF #2 GIRTS @ 16"oc

③ 2x6 BLOCKING BETWEEN
EVERY GIRT

④ (3) LAYERS 5/8" EXTERIOR
MOISTURE RESISTANT
TYPE X GYPSUM BOARD

16'-0"

STEEL LINER PANEL OVER GYPSUM

STEEL LINER PANEL OVER GYPSUM

D-2 TRIM

33" WAINSCOT

2'-1 1/2"
2x8 SYP #1 TREATED
GRADEBOARD

4" CONCRETE FLOOR
(BY OTHERS)

BOTTOM TRIM

?
4 FIREWALL SECTION