


JOB: 13716 - BARTEK

REPRESENTATIVE: RUDI KOVACKO & ASSOCIATES

UNIT TAG:
ENGINEER:
CONTRACTOR:

ORDER NO.
SUBMITTED BY:
APPROVED BY:

DATE: 5/6/2016
DATE:
DATE:



10X12X12XL Series HSC-S Base Mounted - Double Suction Centrifugal Pumps

SPECIFICATIONS

FLOW 3000 HEAD 30
HP 30.00 RPM 1175
VOLTS 575
CYCLE 60 PHASE 3
ENCLOSURE TEFC
APPROX. WEIGHT N/A
SPECIALS

MATERIALS OF CONSTRUCTION

- ☒ Cast Iron Bronze Fitted
- ☒ Fabricated Heavy Duty Baseplate
- ☒ ANSI/OSHA Coupling Guard
- ☒ Flexible Coupling
- ☐ Spacer Coupling (Optional)
- ☐ Galvanized Drip Pan (Optional)

TYPE OF SEAL

☒ **STANDARD:** 175 PSIG (12 Bar) working pressure, 125# ANSI Flange Configuration

☒ **STANDARD:** Crane Type 21, BUNA/Carbon Ceramic, 75 psig (5 Bar) maximum suction pressure, from -20° to 225°F (-29 °C to 107 °C).

☐ **OPTIONAL:** Crane Type 21, EPD/Carbon Ceramic, 75 psig (5 Bar) maximum suction pressure, from -20° to 250°F (-29 °C to 121 °C).

☐ **OPTIONAL:** Crane Type 21, EPD/Carbon Tungsten Carbide, 75 psig (5 Bar) maximum suction pressure, from -20° to 250°F (-29 °C to 121 °C).

☐ **OPTIONAL:** 280 PSIG (19 Bar) working pressure, 250# ANSI Flange Configuration

☐ **STANDARD:** Crane Type 1, BUNA/Carbon-Ceramic, 150 psig (10 Bar) maximum suction pressure, from -20° to 225°F (-29 °C to 107 °C).

☐ **OPTIONAL:** 400 PSIG (27 Bar) working pressure, 250# ANSI Flange Configuration

☐ **STANDARD:** Crane Type 1B, BUNA/Carbon-Ceramic, 300 psig (20 Bar) maximum suction pressure, from -20° to 225°F (-29 °C to 107 °C).

☐ **OTHER:**

