

Network interface

SIP provider1

Name

Trunk group

6

( ) Go to trunk group

Maximum incoming calls

8

Provider authentication

With one account

Bandwidth control area

Default Area

Registrar

Registrar host name

Registrar port

5060

Registrar IP address

Preferred registration interval

3000

Proxy

Use DNS\_SRV (RFC 3263)

Primary proxy

☐ Use primary proxy as outbound

Secondary proxy

DNS SRV record for proxy server

SIP signalling

Use '+' as international prefix

Try to make external calls: Timeout (s)

8

'From' field for CLIR

As defined in SIP account (RFC 3323).

Send session refresh (RFC 4028)

Use destination URL from

'To' field

Music on hold

Music on hold: Signalling

According to RFC3264

Send redirecting information

Yes, using 'Diversion header (recurring)'

Preferred codec

G.711a

Call transfer mode

Re-INVITE

Relay RTP data via communication server for trunk-trunk connections (indirect switching)

Identity (RFC 3325)

PAI P-Asserted-Identity

PPI/PAI header content

SIP ID

Ignore 'Display name'

None

Use originator URL from

PAI header

PRACK support (RFC 3262)

Use SAVP for SRTP

Passive support of 'Precondition' mechanism

Include 'Digest' in each SIP request

Event Package for Registrations (RFC 3680)

NAT

Enable keep alive

ALG support

Relay RTP data via communication server (indirect switching)

Transport protocol

Transport protocol

UDP

SIP accounts

SIP accounts

New

SIP account	SIP ID	User name	DDI(DID) number	Registered
1			-	

General

SIP provider

1 -

SIP account

1

Name

Display name

SIP ID

User name

Password

.....

☐ Show password

Registration

Registration required

Registered

Default account

Presentation

DDI(DID) number

'From' field: Type

SIP ID

'From' field: String

'Contact' field: Type

'From' field

Signal user CLIP in 'From' field