

4.1.1 Extension Settings

1.1 Slot

Shelf Property - Virtual IP Gateway

GW Settings

OK(O)

Cancel(C)

Apply(A)

Main Option 1 Option 2 Option 3

No.	GW Name (20 characters)	Voice Activity Detection for G.711	Reserved	Fax Sending Method	Maximum Bit Rate	FAX Detection Ability	DTMF
1		Enable					
2		Disable	Disable	G.711 Inband	No Speed Limit	Enable	Outband(H.245)
3		Disable	Disable	G.711 Inband	No Speed Limit	Enable	Outband(H.245)
4		Disable	Disable	G.711 Inband	No Speed Limit	Enable	Outband(H.245)
5		Disable	Disable	G.711 Inband	No Speed Limit	Enable	Outband(H.245)
6		Disable	Disable	G.711 Inband	No Speed Limit	Enable	Outband(H.245)
7		Disable	Disable	G.711 Inband	No Speed Limit	Enable	Outband(H.245)
8		Disable	Disable	G.711 Inband	No Speed Limit	Enable	Outband(H.245)
9		Disable	Disable	G.711 Inband	No Speed Limit	Enable	Outband(H.245)
10		Disable	Disable	G.711 Inband	No Speed Limit	Enable	Outband(H.245)
11		Disable	Disable	G.711 Inband	No Speed Limit	Enable	Outband(H.245)
12		Disable	Disable	G.711 Inband	No Speed Limit	Enable	Outband(H.245)
13		Disable	Disable	G.711 Inband	No Speed Limit	Enable	Outband(H.245)
14		Disable	Disable	G.711 Inband	No Speed Limit	Enable	Outband(H.245)
15		Disable	Disable	G.711 Inband	No Speed Limit	Enable	Outband(H.245)
16		Disable	Disable	G.711 Inband	No Speed Limit	Enable	Outband(H.245)
17		Disable	Disable	G.711 Inband	No Speed Limit	Enable	Outband(H.245)
18		Disable	Disable	G.711 Inband	No Speed Limit	Enable	Outband(H.245)
19		Disable	Disable	G.711 Inband	No Speed Limit	Enable	Outband(H.245)
20		Disable	Disable	G.711 Inband	No Speed Limit	Enable	Outband(H.245)
21		Disable	Disable	G.711 Inband	No Speed Limit	Enable	Outband(H.245)
22		Disable	Disable	G.711 Inband	No Speed Limit	Enable	Outband(H.245)
23		Disable	Disable	G.711 Inband	No Speed Limit	Enable	Outband(H.245)
24		Disable	Disable	G.711 Inband	No Speed Limit	Enable	Outband(H.245)
25		Disable	Disable	G.711 Inband	No Speed Limit	Enable	Outband(H.245)
26		Disable	Disable	G.711 Inband	No Speed Limit	Enable	Outband(H.245)
27		Disable	Disable	G.711 Inband	No Speed Limit	Enable	Outband(H.245)
28		Disable	Disable	G.711 Inband	No Speed Limit	Enable	Outband(H.245)
29		Disable	Disable	G.711 Inband	No Speed Limit	Enable	Outband(H.245)
30		Disable	Disable	G.711 Inband	No Speed Limit	Enable	Outband(H.245)
31		Disable	Disable	G.711 Inband	No Speed Limit	Enable	Outband(H.245)
32		Disable	Disable	G.711 Inband	No Speed Limit	Enable	Outband(H.245)
33		Disable	Disable	G.711 Inband	No Speed Limit	Enable	Outband(H.245)
34		Disable	Disable	G.711 Inband	No Speed Limit	Enable	Outband(H.245)
35		Disable	Disable	G.711 Inband	No Speed Limit	Enable	Outband(H.245)
36		Disable	Disable	G.711 Inband	No Speed Limit	Enable	Outband(H.245)
37		Disable	Disable	G.711 Inband	No Speed Limit	Enable	Outband(H.245)
38		Disable	Disable	G.711 Inband	No Speed Limit	Enable	Outband(H.245)
39		Disable	Disable	G.711 Inband	No Speed Limit	Enable	Outband(H.245)

Type: TDE650

Level: Master

Version: 007-000

[1. Configuration - 1. Slot - Shelf Property - Virtual IP Gateway - GW Settings]

View(V) Window(W) Help(H)

4.1.1 Extension Settings

1.1 Slot

Shelf Property - Virtual IP Gateway

OK(O) Cancel(C) Apply(A)

Option 1 Option 2 Option 3

No.	GW Name (20 characters)	IP Codec Priority			Packet Sampling Time (G.711A)	Packet Sampling Time (G.711Mu)
		1st	2nd	3rd		
1		G.729A	G.711A	G.711Mu	20 ms	20 ms
2		G.729A	None	None	20 ms	20 ms
3		G.729A	G.711A	G.711Mu	20 ms	20 ms
4		G.729A	None	None	20 ms	20 ms
5		G.729A	None	None	20 ms	20 ms
6		G.729A	None	None	20 ms	20 ms
7		G.729A	None	None	20 ms	20 ms
8		G.729A	None	None	20 ms	20 ms
9		G.729A	None	None	20 ms	20 ms
10		G.729A	None	None	20 ms	20 ms
11		G.729A	None	None	20 ms	20 ms
12		G.729A	None	None	20 ms	20 ms
13		G.729A	None	None	20 ms	20 ms
14		G.729A	None	None	20 ms	20 ms
15		G.729A	None	None	20 ms	20 ms
16		G.729A	None	None	20 ms	20 ms
17		G.729A	None	None	20 ms	20 ms
18		G.729A	None	None	20 ms	20 ms
19		G.729A	None	None	20 ms	20 ms
20		G.729A	None	None	20 ms	20 ms
21		G.729A	None	None	20 ms	20 ms
22		G.729A	None	None	20 ms	20 ms
23		G.729A	None	None	20 ms	20 ms
24		G.729A	None	None	20 ms	20 ms
25		G.729A	None	None	20 ms	20 ms
26		G.729A	None	None	20 ms	20 ms
27		G.729A	None	None	20 ms	20 ms
28		G.729A	None	None	20 ms	20 ms
29		G.729A	None	None	20 ms	20 ms
30		G.729A	None	None	20 ms	20 ms
31		G.729A	None	None	20 ms	20 ms
32		G.729A	None	None	20 ms	20 ms
33		G.729A	None	None	20 ms	20 ms
34		G.729A	None	None	20 ms	20 ms
35		G.729A	None	None	20 ms	20 ms
36		G.729A	None	None	20 ms	20 ms
37		G.729A	None	None	20 ms	20 ms

Type: TDE600

Level: Installer

Command(M)

Select Provider(S)

Add Provider(P)

Main

Account

Register

NAT

Option

Calling Party

Called Party

Voice/FAX

RTP/RTCP

T.38

T.38 Option

DSP

Supplementary Service

-	No.	Shelf	Slot	Port	Connection	User Name (64 characters)	Authentication ID (64 characters)	Authentication Password (32 characters)
	1	Virtual	3	1	INS			
	2	Virtual	3	2	INS			
	3	Virtual	3	3	Fault			
	4	Virtual	3	4	Fault			
	5	Virtual	3	5	Fault			
	6	Virtual	3	6	Fault			
	7	Virtual	3	7	Fault			
	8	Virtual	3	8	Fault			
	9	Virtual	3	9	Fault			
	10	Virtual	3	10	Fault			
	11	Virtual	3	11	Fault			
	12	Virtual	3	12	Fault			
	13	Virtual	3	13	Fault			
	14	Virtual	3	14	Fault			
	15	Virtual	3	15	Fault			
	16	Virtual	3	16	Fault			

T.38											T.38 Option	DSP	Supplementary Service
No.	Shelf	Slot	Port	Connection	Channel Attribute	Provider Name (20 characters)	SIP Server Location		SIP Server Port Number	SIP Se (100 ch			
							Name (100 characters)	IP Address					
1	Virtual	3	1	INS	Basic channel								
2	Virtual	3	2	INS	Additional channel fo...			172.16.1.6	5060				
3	Virtual	3	3	Fault	Not Used				5060				
4	Virtual	3	4	Fault	Not Used				5060				
5	Virtual	3	5	Fault	Not Used				5060				
6	Virtual	3	6	Fault	Not Used				5060				
7	Virtual	3	7	Fault	Not Used				5060				
8	Virtual	3	8	Fault	Not Used				5060				
9	Virtual	3	9	Fault	Not Used				5060				
10	Virtual	3	10	Fault	Not Used				5060				
11	Virtual	3	11	Fault	Not Used				5060				
12	Virtual	3	12	Fault	Not Used				5060				
13	Virtual	3	13	Fault	Not Used				5060				
14	Virtual	3	14	Fault	Not Used				5060				

Command(M) Select Provider(S) Add Provider(P)

Main Account Register NAT Option Calling Party Called Party Voice/FAX RTP/RTCP T.38 T.38 Option DSP Supplementary Service

-	No.	Shelf	Slot	Port	Connection	Register Ability	Register Sending Interval (s)	Un-Register Ability when port INS	Registrar Server		Registrar Server Port Number
									Name (100 characters)	IP Address	
	1	Virtual	3	1	INS	Disable	300	Enable			
	2	Virtual	3	2	INS	Enable	3600	Enable		172.16.1.6	5060
	3	Virtual	3	3	Fault	Enable	3600	Enable			5060
	4	Virtual	3	4	Fault	Enable	3600	Enable			5060
	5	Virtual	3	5	Fault	Enable	3600	Enable			5060
	6	Virtual	3	6	Fault	Enable	3600	Enable			5060
	7	Virtual	3	7	Fault	Enable	3600	Enable			5060
	8	Virtual	3	8	Fault	Enable	3600	Enable			5060
	9	Virtual	3	9	Fault	Enable	3600	Enable			5060
	10	Virtual	3	10	Fault	Enable	3600	Enable			5060
	11	Virtual	3	11	Fault	Enable	3600	Enable			5060
	12	Virtual	3	12	Fault	Enable	3600	Enable			5060
	13	Virtual	3	13	Fault	Enable	3600	Enable			5060
	14	Virtual	3	14	Fault	Enable	3600	Enable			5060
	15	Virtual	3	15	Fault	Enable	3600	Enable			5060
	16	Virtual	3	16	Fault	Enable	3600	Enable			5060

4.1.1 Extension Settings

1.1 Slot

Shelf Property - Virtual IP Gateway

GW Settings

OK(O) Cancel(C) Apply(A)

Main Option 1 Option 2 Option 3

No.	GW Name (20 characters)	Voice Activity Detection for G.711	Reserved	Fax Sending Method	Maximum Bit Rate	FAX Detection Ability	DTMF
1	Tehran	Enable	Disable	G.711 Inband	No Speed Limit	Enable	Outband(H.245)
2	Tehran new	Disable	Disable	G.711 Inband	No Speed Limit	Enable	Outband(H.245)
3	test siraf	Disable	Disable	G.711 Inband	No Speed Limit	Enable	Outband(H.245)
4		Disable	Disable	G.711 Inband	No Speed Limit	Enable	Outband(H.245)
5		Disable	Disable	G.711 Inband	No Speed Limit	Enable	Outband(H.245)
6		Disable	Disable	G.711 Inband	No Speed Limit	Enable	Outband(H.245)
7		Disable	Disable	G.711 Inband	No Speed Limit	Enable	Outband(H.245)
8		Disable	Disable	G.711 Inband	No Speed Limit	Enable	Outband(H.245)
9		Disable	Disable	G.711 Inband	No Speed Limit	Enable	Outband(H.245)
10		Disable	Disable	G.711 Inband	No Speed Limit	Enable	Outband(H.245)
11		Disable	Disable	G.711 Inband	No Speed Limit	Enable	Outband(H.245)
12		Disable	Disable	G.711 Inband	No Speed Limit	Enable	Outband(H.245)
13		Disable	Disable	G.711 Inband	No Speed Limit	Enable	Outband(H.245)
14		Disable	Disable	G.711 Inband	No Speed Limit	Enable	Outband(H.245)
15		Disable	Disable	G.711 Inband	No Speed Limit	Enable	Outband(H.245)
16		Disable	Disable	G.711 Inband	No Speed Limit	Enable	Outband(H.245)
17		Disable	Disable	G.711 Inband	No Speed Limit	Enable	Outband(H.245)
18		Disable	Disable	G.711 Inband	No Speed Limit	Enable	Outband(H.245)
19		Disable	Disable	G.711 Inband	No Speed Limit	Enable	Outband(H.245)
20		Disable	Disable	G.711 Inband	No Speed Limit	Enable	Outband(H.245)
21		Disable	Disable	G.711 Inband	No Speed Limit	Enable	Outband(H.245)
22		Disable	Disable	G.711 Inband	No Speed Limit	Enable	Outband(H.245)
23		Disable	Disable	G.711 Inband	No Speed Limit	Enable	Outband(H.245)
24		Disable	Disable	G.711 Inband	No Speed Limit	Enable	Outband(H.245)
25		Disable	Disable	G.711 Inband	No Speed Limit	Enable	Outband(H.245)
26		Disable	Disable	G.711 Inband	No Speed Limit	Enable	Outband(H.245)
27		Disable	Disable	G.711 Inband	No Speed Limit	Enable	Outband(H.245)
28		Disable	Disable	G.711 Inband	No Speed Limit	Enable	Outband(H.245)
29		Disable	Disable	G.711 Inband	No Speed Limit	Enable	Outband(H.245)
30		Disable	Disable	G.711 Inband	No Speed Limit	Enable	Outband(H.245)
31		Disable	Disable	G.711 Inband	No Speed Limit	Enable	Outband(H.245)
32		Disable	Disable	G.711 Inband	No Speed Limit	Enable	Outband(H.245)
33		Disable	Disable	G.711 Inband	No Speed Limit	Enable	Outband(H.245)
34		Disable	Disable	G.711 Inband	No Speed Limit	Enable	Outband(H.245)
35		Disable	Disable	G.711 Inband	No Speed Limit	Enable	Outband(H.245)
36		Disable	Disable	G.711 Inband	No Speed Limit	Enable	Outband(H.245)
37		Disable	Disable	G.711 Inband	No Speed Limit	Enable	Outband(H.245)
38		Disable	Disable	G.711 Inband	No Speed Limit	Enable	Outband(H.245)
39		Disable	Disable	G.711 Inband	No Speed Limit	Enable	Outband(H.245)
		Disable	Disable	G.711 Inband	No Speed Limit	Enable	Outband(H.245)

Type: TDE450

Level: Initiation

Version: 007-000