



To:
Cc:
Bcc:
Subject: Trunk Group

Trunk	State	Direction	Time	Agent Name	Extn	Split/Skill	VDN Name
102V01003	IDLE		329:54				
102V01002	IDLE		329:52				
102V01001	SEIZED	IN	2793:46				5551010
102V01004	SEIZED	IN	2669:29				5551010

Time	Inbound Calls	ACD Calls	Inbound Aban Calls	Other Calls	Avg Inbound Trunk Hold Time	Inbound CCS	Outb Ca
Totals	23	0	7	16	44:07	792.00	
12:00 - 12:15AM	0	0	0	0		18.00	
12:15 - 12:30AM	0	0	0	0		18.00	
12:30 - 12:45AM	0	0	0	0		18.00	
12:45 - 1:00AM	0	0	0	0		18.00	
1:00 - 1:15AM	0	0	0	0		18.00	
1:15 - 1:30AM	0	0	0	0		18.00	
1:30 - 1:45AM	0	0	0	0		18.00	
1:45 - 2:00AM	0	0	0	0		18.00	
2:00 - 2:15AM	0	0	0	0		18.00	
2:15 - 2:30AM	0	0	0	0		18.00	
2:30 - 2:45AM	0	0	0	0		18.00	
2:45 - 3:00AM	0	0	0	0		18.00	
3:00 - 3:15AM	0	0	0	0		18.00	
3:15 - 3:30AM	0	0	0	0		18.00	
3:30 - 3:45AM	0	0	0	0		18.00	
3:45 - 4:00AM	0	0	0	0		18.00	
4:00 - 4:15AM	0	0	0	0		18.00	
4:15 - 4:30AM	0	0	0	0		18.00	
4:30 - 4:45AM	0	0	0	0		18.00	
4:45 - 5:00AM	0	0	0	0		18.00	
5:00 - 5:15AM	0	0	0	0		18.00	
5:15 - 5:30AM	0	0	0	0		18.00	
5:30 - 5:45AM	0	0	0	0		18.00	
5:45 - 6:00AM	0	0	0	0		18.00	
6:00 - 6:15AM	0	0	0	0		18.00	
6:15 - 6:30AM	0	0	0	0		18.00	
6:30 - 6:45AM	0	0	0	0		18.00	
6:45 - 7:00AM	0	0	0	0		18.00	
7:00 - 7:15AM	0	0	0	0		18.00	
7:15 - 7:30AM	0	0	0	0		18.00	
7:30 - 7:45AM	0	0	0	0		18.00	
7:45 - 8:00AM	0	0	0	0		18.00	
8:00 - 8:15AM	0	0	0	0		18.00	



To:
Cc:
Bcc:
Subject:

CURRENT SYSTEM INFORMATION

Software Load: R016x.03.0.141.0
Memory Configuration: Large
Offer Category: A

LAST TRANSLATION LOADED INFORMATION

Software Load: R016x.03.0.124.0
Memory Configuration: Large
Offer Category: A
Platform: 28

TRUNK GROUP INFORMATION

Group Number: 1020 Group Type: co CDR Reports: y
Group Name: Store COR: 909 TN: 102 TAC: 6796
Direction: two-way Outgoing Display? n
Dial Access? n Busy Threshold: 255 Night Service: 555-1010
Queue Length: 0 Country: 1 Incoming Destination: 555-1010
Comm Type: voice Auth Code? n Digit Absorption List:
Prefix-1? y Trunk Flash? n Toll Restricted? y

Trunk Type: loop-start

Group Type: co Trunk Type: loop-start

TRUNK PARAMETERS

Outgoing Dial Type: tone Cut-Through? n
Trunk Termination: rc Disconnect Timing(msec): 500

Auto Guard? n Call Still Held? n Sig Bit Inversion: none
Analog Loss Group: 6 Digital Loss Group: 11
Trunk Gain: high

Disconnect Supervision - In? y Out? n Cyclical Hunt? n
Answer Supervision Timeout: 10 Receive Answer Supervision? n
Administer Timers? y
XOIP Treatment: auto

TRUNK FEATURES

ACA Assignment? n Measured: both
Maintenance Tests? y
Data Restriction? n

Abandoned Call Search? n
Suppress # Outpulsing? n

Charge Conversion: 1
Decimal Point: none Replace Restricted Numbers? n
Currency Symbol: Replace Unavailable Numbers? n
Charge Type: units Receive Analog Incoming Call ID: Bellcore
Per Call CPN Blocking Code:
Per Call CPN Unblocking Code:

Outgoing ANI: Ds1 Echo Cancellation? n

ADMINISTRABLE TIMERS

Send Incoming/Outgoing Disconnect Timers to TN465 Ports? n
Incoming Disconnect(msec): 500 Outgoing Disconnect(msec): 500
Outgoing Dial Guard(msec): 1600
Incoming Glare Guard(msec): 1500 Outgoing Glare Guard(msec): 1500

Ringing Monitor(msec): 5200 Incoming Seizure(msec): 500
Outgoing End of Dial(sec): 10 Outgoing Seizure Response(sec): 5
Programmed Dial Pause(msec): 1500
Flash Length(msec): 540

END TO END SIGNALING

Tone(msec): 350 Pause(msec): 150

OUTPUTSING INFORMATION

PPS: 10 Make(msec): 40 Break(msec): 60 PPM? n

ATMS THRESHOLDS

TTL Type: 105-w-rl Far End Test No:
TTL Vendor: TTL Contact:
Trunk Vendor: Trunk Contact:
Trunk Length:

	MARGINAL		UNACCEPTABLE	
	Min	Max	Min	Max
1004 Hz Loss:	-2	21	-2	21
	-Dev	+Dev	-Dev	+Dev
404 Hz Loss:	9	9	9	9
2804 Hz Loss:	9	9	9	9

Maximum C Message Noise: 55 55
Maximum C Notched Noise: 74 74
Minimum SRL-HI: 0 0
Minimum SRL-LO: 0 0
Minimum ERL: 0 0

Allow ATMS Busyout, Error Logging and Alarming? n