

BCM - Voip.MS settings

Accounts/Basic

Note: when using sub accounts at voip.ms make sure they all use the exact same server

Details for Account:

Basic | Advanced | User Accounts

SIP Domain

Remote:

Local:

Proxy

Address:

Port:

Transport:

Registrar

Address:

Port:

Outbound Proxy Table

Domain	IP Address	Port	Load-balancing Weight	Keep alive
--------	------------	------	-----------------------	------------

Accounts/Advanced

Details for Account:

Basic | Advanced | User Accounts

Enable local NAT compensation:

Enable media relay:

Use maddr in R-URI:

Use maddr in Contact:

Support 100rel:

Allow UPDATE:

Use Null IP to hold:

Use user=phone:

Force E164 international dialing:

Enable SDP OPTIONS query:

Allow REFER:

Support Replaces:

Enable Connected Identity:

Standard SIP Caps Exchange:

NAT Pinhole Maintenance

Signaling method:

Signaling interval:

Session timer

Session refresh method:

Active call limit:

ITSP association method:

Outbound Called characters to absorb:

Inbound Called prefix to prepend:

Authentication realm:

Accounts/UserAccounts/Modify Account

The image shows two side-by-side screenshots of the "Modify account" dialog box. The left window is for a "Parent Account" and the right is for a "Child Account". Both windows have the same layout with fields for Description, Domain, Account identity, User Credentials, Message Handling, and SIP Registration. The "Parent Account" window has "Parent account" checked and "CLID" filled with "5555555555". The "Child Account" window has "Parent account" unchecked and "CLID" filled with "5555555555". The "Message Handling" section in the "Parent Account" window has "CLID Override" filled with "Your user name" and "PAI CLID Override" filled with "Your phone number". The "Child Account" window has "CLID Override" empty and "PAI CLID Override" filled with "Your phone number".

CLID Override – Your user name – This allows an outbound call to go through

PAI CLID Override – Your phone number - Your actual CLID (or use Voip.MS CLID options)

This also allows the outbound call to go through, so both CLID Override and PAI CLID Override need to be filled in and accurate.

If using "child" accounts in the BCM then just the PAI CLID Override is required in Message Handling otherwise both the CLID Override and PAI CLID Override in the "parent" account is used.

PAI Display name Override – Your name of choice – The name passed along with the CLID