


Telco PC - Voip.MS Settings - June 26 2022

General Settings | LAN Interfaces | VLAN Interfaces | Static Routes | Dial-O

System Information
System name:

IP Settings

 **If you change the default gateway you may lose your c**

Default gateway:

Published IP Interface:

Published IP Address:

Public Network

Discovered Public Address:

Address Discovery Flag:

Stun Server Address:

Stun Server Port:

Stun Local Address:

Stun Local Port:

DNS Settings

DNS domain name:

Primary DNS address:

Secondary DNS address:

Configuration | Administration

- Welcome
- System
 - Identification
 - Date and Time
 - Keycodes
 - IP Subsystem
 - Telephony Regions
- Administrator Access
- Resources
 - Application Resource
 - Media Gateways
 - Port Ranges
 - SIP Clients
 - Telephony Resource
- IP Trunks
 - **General**
 - SIP Trunking
 - H323 Trunking

Call Routing Summary | IP Trunk Settings

Telephony Settings

Forward redirected OLI: Send name display:

Remote capability MWI: Ignore in-band DTMF in RTP:

Public Private Global Settings Media Parameters

SIP Settings
Local Domain:

Service Impacting SIP Settings
Call signaling port: 5060

RTP Keepalives
Scope:

Telephony Settings
Fallback to circuit-switched:

RFC2833
Dynamic Payload:

Status: Gateway is running

Configuration Administration SIP Trunking

Public Private Global Settings Media Parameters

Preferred Codescs

Available list

Selected list
G.711-uLaw
G.711-aLaw
G.729

Settings
Enable Voice Activity Detection:
Jitter buffer:
G.729 payload size (ms):
G.711 payload size (ms):
Fax transport:
Force G.711 for 3.1k audio:
Provide in-band ringback:

System

Routing Table Settings Accounts ITSP Templates

Name	Destination Digits	Account
voipms x101	94	VoipMS
s'		
si		
c		

Public Private Global Settings Media Parameters

Routing Table Settings Accounts ITSP Templates

Name	Description
VoipMS	Telco PC - Main Line
Standard	Standard Telephony X324

Add... Delete

Details for Account:

Basic Advanced User Accounts

SIP Domain

Remote: 208.100.60.54

Local:

Proxy

Address: 208.100.60.54

Port: 5060

Transport: UDP

Registrar

Address: 208.100.60.54

Port: 5060

Outbound Proxy Table

Domain	IP Address	Port	Load-balancing Weight

System

- Identification
- Date and Time
- Keycodes
- IP Subsystem
- Telephony Regions
- Administrator Access
- Resources
 - Application Resource
 - Media Gateways
 - Port Ranges
 - SIP Clients
 - Telephony Resource
 - IP Trunks
 - General
 - SIP Trunking
 - H323 Trunking
 - Dial Up Interfaces
- Telephony
- Data Services
- Applications

Routing Table Settings Accounts ITSP Templates

Name	Description
VoipMS	Telco PC - Main Line
Standard	Standard Telephony X324

Add... Delete

Details for Account:

Basic Advanced User Accounts

Enable local NAT compensation:

Enable media relay:

Use maddr in R-URI:

Use maddr in Contact:

Support 100rel:

Allow UPDATE:

Use Null IP to hold:

Use user=phone:

Force E164 international dialing:

Enable SDP OPTIONS query:

Allow REFER:

Support Replaces:

Enable Connected Identity:

Standard SIP Caps Exchange:

NAT Pinhole Maintenance

Signaling method: None

Signaling interval: 30

Session timer

Session refresh method: Disable

Active call limit: 0

ITSP association method: From header domain match

Outbound Called characters to absorb: 2

Inbound Called prefix to prepend:

Authentication realm:

System

- Identification
- Date and Time
- Keycodes
- IP Subsystem
- Telephony Regions
- Administrator Access
- Resources
 - Application Resource
 - Media Gateways
 - Port Ranges
 - SIP Clients
 - Telephony Resource
- IP Trunks
 - General
 - SIP Trunking
 - H323 Trunking

Routing Table Settings Accounts ITSP Templates

Name	Description
VoipMS	Telco PC - Main Line
	Standard Telephony X224

Add... Delete

Details for Account:

Basic Advanced User Accounts

Description	Parent	CLID	SIP Username	Register	Status
X101	<input checked="" type="checkbox"/>		208.100.60.54	<input checked="" type="checkbox"/>	Registered wi...

Credentials for the Sub Account at Voip.MS:

Modify account [X]

Description: X101

Domain: 208.100.60.54

Account identity

Parent account:

User Credentials

SIP username: Your User Name

Auth name: Your User Name

Auth password: ●●●●●●●●●●●●●●●●

Realm:

Message Handling

CLID Override: Your Phone Number or UserName

Display name Override:

PAI CLID Override: Your Phone Number

PAI Display name Override: Your Name

Contact Override:

Maddr in Contact:

Local Domain Override:

Compensate for NAT:

SIP Registration

Registration:

Registration Details

Registrar: 208.100.60.54

Registrar Port: 5060

Transport: UDP

Expiry: 180

OK Cancel